



PREDATOR

Platform Automatic Stretch Wrap System

The Predator Platinum improves productivity by automatically wrapping loads with just a push of the remote. The automatic film attach, cut, and wipe down is the most advanced in the industry and improves productivity by up to 40%.

The Predator Platinum is a true fully automatic system with built-in features for increased productivity that are not available on other simpler automatics.



Low Profile shown High Profile available

HIGHLIGHTS

- » Automation package includes remote control and film clamp, cut, and wipedown
- » Select-Stretch™ offers greater film performance with 230% and 270% gears
- » Touchscreen provides flexible controls, help screens, and allows for future upgrades



CONTROL PANEL FEATURES

- Touch Screen for easy machine setup and help screens
- Start
- Reset
- Stop
- · Adjustable Film Force

- · Adjustable Carriage Speed
- · Adjustable Turntable Speed
- · Emergency Stop
- · Integrated On/Off Switch
- · Lanyard Start/Stop Pull Cord

PREMIUM FEATURES



Automatic Film Clamp, Cut, and Wipedown

Remote control starts wrap cycle. At the end of the cycle the film jaws grip the film and the hot wire pulses to cut the film. The whale tail brushes the film on the load for the best film wipe down in the industry.



Select-Stretch™

Select Stretch™ allows you to quickly changes your pre-stretch level from 230% to 270% with the press of a button.



Side-Mounted Carriage with Fast Film Feed

Side mounted carriage with Fast Film Feed for easy and quick film threading.



Advanced Electrical Controls

The touchscreen controls provide easy user flexibility for program changes and help screens. Control Panel swivels 360° for full viewing from virtually any angle.

SYSTEM SPECIFICATIONS

Pre-Stretch Gears	230% and 270% Selectable	Load Weight Capacity	Low & High Profile 4,000 pounds
Turntable	Low Profile 70" Diameter, 12 RPM High Profile 48"x48" Octagonal, 12 RPM	3 Wrap Modes	Bottom Wraps First, Top Wraps First, Top First with Slow Turntable
Wrap Height	80" Standard, options up to 110"	Machine Weight	Low Profile 1,220 Pounds High Profile 1,500 Pounds
Motors	AC (for lower maintenance)	Pneumatic Requirements	3 cfm @ 80 psi shop air or optional air compressor
Drives	Variable Frequency	Electrical Requirements	115 Volts, 15 Amp

Contact:

