

New!

SIGNODE TableTyer™

Plastic strapping machine

- ***Easy to operate***
- ***Economical***
- ***Portable***

SIGNODE®



A low cost, entry level strapping system from Signode

Simple operation

The TableTyer is easy to set up and operate:

1. Select the strap length and tension on the control panel
2. Place strap around the package, and re-insert the strap end into the machine. The TableTyer automatically removes the slack by pulling the desired tension and joins the strap ends with a secure heat weld. The system automatically feeds another length of strap for the next package or bundle.



Low maintenance

Built with few wearing parts, the TableTyer requires very little maintenance. The 24 VDC motor runs only when the machine is cycling. The heater is "stepped down" to 24 VAC to prolong the life of the heat knife.

Economical

The TableTyer uses our inexpensive Empax™ polypropylene strapping.

Variable tension

The external tension dial can be adjusted from 2 lbs. to 100 lbs.

Heat sealing mechanism

The sensor controlled heat sealing mechanism ensures consistent, high-efficiency seals. Weld cooling time can be adjusted for proper sealing.

Flexible design

The strapping guides are adjustable to use strap sizes from 1/4" to 1/2".

Adjustable height

The table top height is adjustable from 30-3/4" to 37-1/2".

Package stop

Butting the package against the package stop helps ensure tight, straight strap application.



Internal strapping dispenser

Conserves floor space.



Portable

Four locking casters enable the machine to be positioned wherever needed.



Small package option

Enables packages as small as 2"W x 1-1/5"H to be strapped.

TableTyer Specifications



Maximum package weight: 125 lbs.

Strap tension: 2–100 lbs.

Strapping: Empax 1/4", 3/8", and 1/2" plastic strapping

Electrical requirements: 120 volt, 1 phase, 60Hz

Shipping weight: 168 lbs.

SIGNODE®

3610 West Lake Avenue
Glenview, Illinois 60025
1-800-323-2464